PORTWEST

PRODUCT SPECIFICATION & TECHNICAL DATA

EP08 - Corded PU Foam Ear Plug (200

pairs)

Collection: Ear Plugs

Range: PPE

Materials: PU Foam, PVC

Inner Pack: 200 Outer Carton: 10

Product information

Disposable PU ear plug. The tapered shape ensures a comfortable fit inside the ear canal. Corded for extra comfort and easy storage around the neck when not in use. Each pair comes inside a hygienic polybag with fitting instructions.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 352-2 (SNR 36dB) ANSI S3.19 (32dB)



Features

- CE-CAT III
- Retail box which aids presentation for retail sales
- Corded for safe keeping
- Easy to fit
- One pair per hang cell (stored in hygienic polybag)
- Individually packed for vending machines

	Range
Orange	-

PORTWEST

PRODUCT SPECIFICATION & TECHNICAL DATA

EP08 - Corded PU Foam Ear Plug (200 pairs)

Commodity Code: 3926909790

Test House

Michael & Associates, Inc. (Notified Body No.:) 2766 W. College Ave Suite 1 PA 16801, United States

Cert No: Q1441A

ALIENOR CERTIFICATION (Notified Body No.: 2754)

 $ZA\ du\ Sanital$ $86100\ ,\ France$

Cert No: 2754/1246/159/06/18/0288

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m³)	EAN13	DUN14
EP08ORR	Orange	65.0	35.0	33.0	0.7600	0.0751	5036108183852	15036108622419

PORTWEST_®

PRODUCT SPECIFICATION & TECHNICAL DATA

PERFORMANCES - SOUND ATTENUATION - EN352-2:2002

EP02/EP08/EP30										
Α	Frequency (Hz)	125	250	500	1000	2000	4000	8000		
В	Means Attenuation (dB)	36.5	34.2	39.1	37.8	39.6	44.9	46.2		
C	Standard Deviation (dB)	4.7	4.5	4.8	5.8	4.0	6.4	6.2		
D	Assumed Protection (dB)	31.7	29.7	34.2	32.0	35.5	38.5	40.1		
SNR = 36 dB H = 36 dB / M = 33 dB / L = 32 dB										

PERFORMANCES - SOUND ATTENUATION ANSI S.19-1974

Tested by Michael & Associates, Inc. – 400 Long Lane, PA Furnace, PA 16865, USA

EP0	EP02/EP08									
Α	Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
В	Means Attenuation (dB)	39.8	40.4	42.6	40.3	39.1	45.2	45.7	48.3	47.4
C	Standard Deviation (dB)	3.0	3.9	2.9	3.6	3.7	3.0	2.5	4.9	3.7
NRR (Noise Reduction Rating) = 32 dB										

EP08ORR